Category 6E Shielded Tool-Less RJ-45 Keystone Jacks

Transmission and Electrical Specifications

FREQ.	Insertion Loss	NEXT	FEXT	RL
MHz	dB	dB	dB	dB
	Max	Min	Min	Min
1.00	0.02	85.0	84.0	53.0
4.00	0.02	81.0	75.0	54.0
8.00	0.02	78.0	70.0	56.0
10.00	0.03	77.0	68.0	57.0
16.00	0.03	73.0	58.0	58.0
25.00	0.04	70.0	60.1	60.0
31.25	0.04	68.0	59.0	57.0
62.50	0.05	64.0	53.0	44.0
100.00	0.06	60.0	49.0	34.0
200.00	0.06	55.0	43.0	23.0
250.00	0.08	52.0	41.0	20.0

Typical De-Embedded Return-Loss



Propagation Delay	2.5 nS max @ 1-250 MHz
Propagation Delay Skew	1.25 nS max @ 1-250 MHz
Current rating	1.5 A max.
Contact resistance	20 mOhm max (per contact)
Input/Output resistance	200 mOhm max
Input/Output resistance Unbalance	50 mOhm max
Voltage rating	72 Vdc max
Dielectric strength	1000 Volts rms for 1 minute
Insulation Resistance	500 MegaOhm min @ 500 Vdc
DC Resistance	0.1 Ohm max @ 20C
TCL	28-20·Log(f/100) dB min @ 1-250 MHz
Transfer Impedance	0.1 Ohm @ 1 MHz, 0.2 Ohm @ 10 MHz, 1.6 Ohm @ 80 MHz max.

Typical De-Embedded Insertion-Loss



Typical De-Embedded FEXT-Loss



Ordering Information

HCS P/N	Description	Orientation	T568
J6E-00861	8P8C RJ-45 Shielded Tool-less Keystone Jack CAT 6E	90°	B
J6E-00862	8P8C RJ-45 Shielded Tool-less Keystone Jack CAT 6E	90°	A
J6E-00863	8P8C RJ-45 Shielded Tool-less Keystone Jack CAT 6E	90°	Universal